

SLIM CANOPY

naturaLED® (SCM) Slim canopy is DLC Premium listed and ETL for wet locations with a rating of IP65. Aesthetically pleasing construction, low-profile design with die-cast aluminum housing and shatter-resistant polycarbonate prismatic lens. Dustproof, sealed structure, ½" threaded conduit entrances on each side. This fixture comes with or without an integral microwave occupancy sensor, factory mounted behind the lens. The microwave occupancy sensor has multiple sensor settings that can be selected via dip switch at the sensor brain inside the fixture which include: daylight sensing, step dimming, area sensitivity, standby time and on/off.

The canopy supports both pendant mounting and direct surface mounting ceiling and wall. The Slim Canopy fixture can be Pendant Mounted and accepts a ¾" NPT Thread and can be mounted to multiple types of J-boxes. Ideal applications for parking garage, canopy, walkway and entrance lighting etc.



Features & Benefits

- ▶ DLC Premium Qualified
- ▶ IP65 Rated
- ▶ Multiple sensor settings
- ▶ Long life LED chips
- ▶ Uniform and consistent color
- ▶ Excellent thermal design
- ▶ Shatter-resistant polycarbonate lens
- ▶ Finish: Aluminum die-cast

Specifications

- ▶ Input line voltage: 120-277V
- ▶ Powerfactor >0.9
- ▶ Operating temperature: -40°F ~ 122°F
- ▶ 50,000 hrs rated average life

Applications

- ▶ Warehouses
- ▶ Offices
- ▶ Factories
- ▶ Hospitals
- ▶ Hotels

Color Choices



Optional Accessories

- ▶ Drop Lens



- ▶ Frosted Lens



Ordering Information

*P= DLC Premium / S = Standard DLC

	Code	Description	CCT	Watt	Lumen	Equiv Wattage	Color	Beam Angle	Sensor	Rated Hrs	IP65	DLC
Microwave Motion Sensor	7489	LED-FXSCM28/40K/BK-SEN	4000K	28	3,236	150	Black	160°	Yes	50,000	•	P
	7490	LED-FXSCM28/50K/BK-SEN	5000K	28	3,375	150	Black	160°	Yes	50,000	•	P
	7491	LED-FXSCM42/40K/BK-SEN	4000K	42	4,871	175	Black	160°	Yes	50,000	•	P
	7492	LED-FXSCM42/50K/BK-SEN	5000K	42	5,003	175	Black	160°	Yes	50,000	•	P
	7493	LED-FXSCM59/40K/BK-SEN	4000K	59	6,800	250	Black	160°	Yes	50,000	•	P
	7494	LED-FXSCM59/50K/BK-SEN	5000K	59	6,985	250	Black	160°	Yes	50,000	•	P
	7480	LED-FXSCM28/50K/WH-SEN	5000K	28	3,375	150	White	160°	Yes	50,000	•	P
	7482	LED-FXSCM42/50K/WH-SEN	5000K	42	5,003	175	White	160°	Yes	50,000	•	P
	7484	LED-FXSCM59/50K/WH-SEN	5000K	59	6,985	250	White	160°	Yes	50,000	•	P
	7468	LED-FXSCM28/40K/BK	4000K	28	3,236	150	Black	160°	-	50,000	•	P
	7469	LED-FXSCM28/50K/BK	5000K	28	3,375	150	Black	160°	-	50,000	•	P
	7470	LED-FXSCM42/40K/BK	4000K	42	4,871	175	Black	160°	-	50,000	•	P
	7471	LED-FXSCM42/50K/BK	5000K	42	5,003	175	Black	160°	-	50,000	•	P
	7472	LED-FXSCM59/40K/BK	4000K	59	6,800	250	Black	160°	-	50,000	•	P
	7473	LED-FXSCM59/50K/BK	5000K	59	6,985	250	Black	160°	-	50,000	•	P
	7495	LED-FXSCM28/40K/WH	4000K	28	3,236	150	White	160°	-	50,000	•	P
	7496	LED-FXSCM28/50K/WH	5000K	28	3,375	150	White	160°	-	50,000	•	P
	7497	LED-FXSCM42/40K/WH	4000K	42	4,871	175	White	160°	-	50,000	•	P
	7498	LED-FXSCM42/50K/WH	5000K	42	5,003	175	White	160°	-	50,000	•	P
	7499	LED-FXSCM59/40K/WH	4000K	59	6,800	250	White	160°	-	50,000	•	P
	7500	LED-FXSCM59/50K/WH	5000K	59	6,985	250	White	160°	-	50,000	•	P

Accessories (available for purchase)

Lens

P10126 LENS-SCM/DR9X9

Slim Canopy Clear Drop Lens

Drop Lens Measurements:
9" x 9" (228mm x 228mm)




P10125 LENS-SCM/FR9X9

Slim Canopy Frosted Lens



Photometric Data


28 Watt- Slim Lens




Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	545.95	16.90
0-40	973.72	30.10
0-60	2033.15	62.80
60-80	939.05	29.00
70-80	433.05	13.40
90-120	37.98	1.20
90-180	43.04	1.30
0-180	3237.05	100.00

Total Luminaire Efficiency = 100.00%




42 Watt- Slim Lens




Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	808.51	16.60
0-40	1450.8	29.80
0-60	3045.56	62.50
60-80	1425.98	29.30
70-80	653.33	13.40
90-120	54.92	1.10
90-180	63.28	1.30
0-180	4873.43	100.00

Total Luminaire Efficiency = 100.00%




59 Watt- Slim Lens




Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1154.02	17.00
0-40	2096.9	30.80
0-60	4418.05	65.00
60-80	1851.99	27.20
70-80	796.49	11.70
90-120	106.83	1.60
90-180	117.96	1.70
0-180	6801.88	100.00

Total Luminaire Efficiency = 100.00%




28 Watt- Tall Lens




Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	725.76	24.70
0-40	1180.00	40.10
0-60	2028.37	68.90
60-80	603.32	20.50
70-80	232.84	7.90
90-120	160.48	5.50
90-180	231.64	7.90
0-180	2944.02	100.00

Total Luminaire Efficiency = 100.00%




42 Watt- Tall Lens




Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1121.56	24.60
0-40	1824.37	40.10
0-60	3140.64	69.00
60-80	929.66	20.40
70-80	355.68	7.80
90-120	248.18	5.50
90-180	358.05	7.90
0-180	4552.49	100.00

Total Luminaire Efficiency = 100.00%



59 Watt- Tall Lens



Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	1442.75	25.20
0-40	2338.87	40.80
0-60	3988.9	69.60
60-80	1148.22	20.00
70-80	432.00	7.50
90-120	314.07	5.50
90-180	434.75	7.60
0-180	5731.02	100.00



Total Luminaire Efficiency = 100.00%



Product Dimensions



28-Watt

Weight: 4.50-lbs



42/59-Watt

Weight: 5.10-lbs



Package



Package
(Master)

1