

ProLED_® ECO Downlights











ProLED 4" and 6" downlights are high in performance at a low cost



Reliable Performance in a Budget-Friendly Design

Replaces up to 65 Watt Incandescent (85% Energy Savings)

Dimmable

5-Year Limited Warranty

ENERGY STAR® Certified

Applications:

Homes

Education

Healthcare

Hospitality

Office

Markets:

Residential

Commercial



Contact Your Customer Care Specialist For Pricing, Orders And Technical Support.



Product #:	Type:	
Project:	Date:	
Comments:	Initials:	


Specifications

- 50,000 hour life results in lower maintenance costs over time
- Acceptable for use in insulated contact airtight (ICAT) rated recessed housings
- Dimmable to 10%
- CRI 90
- CA JA8 listed for High Efficacy LED Sources
- ENERGY STAR® Certified
- 4" Luminaire is UL approved for damp locations
- 6" Luminaire is UL approved for wet locations
- RoHS Compliant


Standard with both models: Title 24 compliant quick plug connector plugs directly into dedicated LED recessed housings



4" version for mounting into 4" recessed housings



4" Model



6" Model



Available GU24 socket base adapter sold separately

Ordering Information











	Watt	Product #	Product Code	Volts	Color Temp.	CRI	Lumens	Useful Life*	Dimmable	Pkg. Qty.	Fixture Size	Beam Spread	Equivalent Wattage
٥	10	99633	DL4FR10/927/ECO/LED2	120	2700	90	650	50,000	Yes	1/12	4"	90°	50
٥	10	99634	DL4FR10/930/ECO/LED2	120	3000	90	650	50,000	Yes	1/12	4"	90°	50
٥	10	99635	DL4FR10/940/ECO/LED2	120	4000	90	650	50,000	Yes	1/12	4"	90°	50
٥	10	99636	DL4FR10/950/ECO/LED2	120	5000	90	650	50,000	Yes	1/12	4"	90°	50
٥	10	99637	DL6FR10/927/ECO/LED2	120	2700	90	650	50,000	Yes	1/6	6"	90°	65
٥	10	99638	DL6FR10/930/ECO/LED2	120	3000	90	650	50,000	Yes	1/6	6"	90°	65
٥	10	99639	DL6FR10/940/ECO/LED2	120	4000	90	650	50,000	Yes	1/6	6"	90°	65
٥	10	99640	DL6FR10/950/ECO/LED2	120	5000	90	650	50,000	Yes	1/6	6"	90°	65
٥	12	99641	DL6FR12/927/ECO/LED2	120	2700	90	800	50,000	Yes	1/6	6"	90°	75
٥	12	99642	DL6FR12/930/ECO/LED2	120	3000	90	800	50,000	Yes	1/6	6"	90°	75
0	12	99643	DL6FR12/940/ECO/LED2	120	4000	90	800	50,000	Yes	1/6	6"	90°	75
٥	12	99644	DL6FR12/950/ECO/LED2	120	5000	90	800	50,000	Yes	1/6	6"	90°	75
٥	15	99645	DL6FR15/927/ECO/LED2	120	2700	90	1,100	50,000	Yes	1/6	6"	90°	100
٥	15	99646	DL6FR15/930/ECO/LED2	120	3000	90	1,100	50,000	Yes	1/6	6"	90°	100
٥	15	99647	DL6FR15/940/ECO/LED2	120	4000	90	1,100	50,000	Yes	1/6	6"	90°	100
٥	15	99648	DL6FR15/950/ECO/LED2	120	5000	90	1,100	50,000	Yes	1/6	6"	90°	100
		91003	ADP/DL/GU24/LED	GU24 Sc	ocket Adapter								

May not be compatible with all dimming systems, dimming performance may vary by system, please check the website www.halcolighting.com/ProLEDdim for up-to-date dimmer compatibility information. Use on incompatible dimming systems may shorten lamp life

Useful Life is defined as the point in time at which the LED will maintain at least 70% of its initial lumens. The LED will continue to burn past this point, but at decreased light levels. . Warranty - Commercial / Industrial: This product is warranted for 5 years from the date of purchase